

FOOD PE

EPD
INTERNATIONAL EPD SYSTEM

TÜV SÜD

TECHNICAL DATA


HIGH SPEED
Up to 2 m/s


HIGH SAFETIES


SELF-REPAIRING


OIL FREE



POLYETHYLENE CURTAIN
ALIMENTARY


WASHABLE


GRAVITY
TECHNOLOGY

MAXIMUM DIMENSIONS	**W** 4500 mm x **H** 3800 mm
SPEED	**Max opening speed** Up to 2 m/s
	Closing speed 0,6 m/s
CYCLES TEST	1.000.000
WIND RESISTANCE	Class 0
STRUCTURE	Not self-supporting
FRAME	**Standard** Polyethylene HD 1.000.000
MOTOR COVER	Stainless Steel
CURTAIN	**Standard** PVC curtain 1300 gr/m², 6 W/m²K
	Optional • Translucent 35/40% • FDA (white) • Antistatic
SLIDING SYSTEM	Patented sliding system with high density Polyzene self-lubricant equipped of sliding zipper directly on curtain
CONTROL PANEL	**Standard** PVC box IP65 (300 x 400 x 150 mm)
	Optional • Stainless Steel • Powder coated steel box IP54 (300 x 500 x 150 mm)
	Inverter system 50/60 Hz with absolute encoder
	Power supply 1-ph, 230V max 16A
	Power supply 3-ph, 400V max 10A
	Power supply 3-ph, 230V max 16A
	Start/ Stop button
	2 free contacts (door open/closed/alert)
	Automatic/ Manual Interlocking between 2 doors
	IP rating for motor and control panel IP54
WIRING	Plug and Play system IP65
SAFETIES	**Standard** • Photocells set IP65 • Anti-jam sensor reverse
	Optional • WiFi safety edge IP65
EMERGENCY OPENING	**Standard** Hand crank
	Optional • Chain system • UPS battery
ADVISING OPERATIVE TEMPERATURE	Operating till positive temperature (> 0°C) Not apt to be installed in negative/positive temperature

DynamicRoll® FOOD PE is a self-repairing roll up door studied to environments, where hygiene is the most important issue. Its Polyethylene frame is designed to be sanitized in all its parts, without removal or disassembly of any profiles or covers with related problems in assembling again all screws and external elements.
Columns come out from a Polyethylene monolithic section, where the zippers on the curtain run inside.
The specifically designed zip guide system allows the curtain to exit the guides in the event of impact and reinsert in one cycle.

For more information, download the complete datasheet

CLICK HERE

PVC CHARACTERISTICS

STANDARD PVC

Composition and tests

EXTERNAL SIDE			
Material	*Finishing*	*Color*	*Thick*
PVC	Opaque	18 standard	0,7 mm
FABRIC			
Material	*N. tarps*	*Title*	*EN 2286-2*
PES	1	1100Dtex 12x12	900 g/m²
INTERNAL SIDE			
Material	*Finishing*	*Color*	*Thick*
PVC	Rough	18 standard	0,2 mm

Characteristics

THICK
ISO 2286/3
(mm) 0,9±0,1

WEIGHT
ISO 2286/2
(kg/m2) 0,90±0,1

Colors



Translucent Antistatic available
FDA (Food Drug Administration) certificated pvc available

INSULATED PVC

Composition and tests

EXTERNAL SIDE			
Material	*Finishing*	*Color*	*Thick*
PVC	Straight	6 standard	0,5 mm
FABRIC			
Material	*N. tarps*	*Title*	*EN 2286-2*
PES	1	1100Dtex 12x12	1350 g/m²
INTERNAL SIDE			
Material	*Finishing*	*Color*	*Thick*
PVC	Sponge	6 standard	7 mm

Characteristics

THICK
ISO 2286/3
(mm) 7,0±0,1

WEIGHT
ISO 2286/2
(kg/m2) 1,7±0,1

Colors



CRISTAL CHARACTERISTICS
PVC SUPERCLEAR



SUITABLE ONLY FOR POSITIVE TEMPERATURE ENVIRONMENTS

WINDOWS - *CRISTAL*
TECHNICAL DATA

Article	SUPERCLEAR 0.75 mm FR

Technical specifications	Standards	Unit	Values
Thickness	-	mm.	0.75
PVC total weight	-	g/m2	940
Light transmission	JIS K - 7361	%	87.5

FDA CERTIFICATED PVC
Food Drug Administration

TECHNICAL DATA

Composition and tests

TOP FACE COATING			
Material	*Finish*	*Color*	*Thickness*
PUR	Opaque	White	0,6 mm
FABRIC			
Material	*N. tarps*	*Title*	*EN 2286-2*
PET	1	2200 Dtex 12x12	1500 g/m²
UNDERSIDE COATING			
Material	*Finish*	*Color*	*Thickness*
PUR	Plain	White	0,6 mm

Characteristics

THICKNESS
ISO 2286/3
(mm) 1,20±0,1

WEIGHT
ISO 2286/2
(kg/m2) 1,30±0,1

TENSILE STRENGTH WARP
ISO 1421
6000 N / 50mm

Disclaimer

The information contained in this document describes the features of the BMP EUROPE product as tested in a laboratory, other indications excepted, environment at a temperature of +23 degrees °C at 50% relative humidity. It does not necessarily reflect the conditions of industrial use and it does not guarantee the product to be suitable for certain applications. The client remains liable for the proper selection and correct use of the BMP EUROPE product. BMP EUROPE cannot be held responsible should damages arise from the use of its products. Necessary alterations to this data can be made without prior notice.

OPTIONAL ACCESSORIES

RADAR



OPENING POINTING RADAR
TOF/SPOT
for internal use only



INFRARED RADAR
with cross-movement
adjustment



INFRARED RADAR
motion and presence
(pedestrian/forklift) radar

TRAFFIC LIGHTS



GREEN FIXED STANDARD
traffic light



RED FIXED STANDARD
traffic light



LED TRAFFIC LIGHT
with countdown



LED TRAFFIC LIGHT BARRIERS
(connection card included)

BUTTONS



OPENING GREEN BUTTON
with box



OPENING BLACK BUTTON
with box



FREEZE STOP BUTTON
with box



NO TOUCH BUTTON



TRAFFIC LIGHT BUTTON
DUAL-FUNCTION
opening and
intermittent door
opening/closing
signaling



WIND GAUGE



KEY SELECTOR



REMOTE CONTROL



BOLLARD B-PROTECT



PULL CORD SWITCH



MAGNETIC LOOP DETECTOR

Quality products since 1997

BMP EUROPE HIGH SPEED DOORS
Strada della Freisa 1 - Villanova d'Asti 14019 (AT)
+39 0141 948843
www.bmpdoors.com - info@bmpeurope.eu

09/2026